











Curvado Glazed Range Technical Data Sheet

BRICKWORKS

Product Range	Product Name	Swatch	State	Length (mm)	Width (mm)	Height (mm)	Average Weight / Unit (kg)	Units per Square Metre	Pack Size	LRV
Curvado Glazed	Bottle Green		NSW	470	286	75	3.9	11.4	180	
Curvado Glazed	White		NSW	470	286	75	3.9	11.4	180	
Curvado Glazed	Black		NSW	470	286	75		11.4	180	
Curvado Glazed	Carminie		NSW	470	286	75	3.9	11.4	180	6.8
Curvado Glazed	Cobalt Azul		NSW	470	286	75	3.9	11.4	180	
Curvado Glazed	Cognac		NSW	470	286	75	3.9	11.4	180	
Curvado Glazed	Honey		NSW	470	286	75	3.9	11.4	180	
Curvado Glazed	Olive Green		NSW	470	286	75	3.9	11.4	180	
Curvado Glazed	Trans Hispania		NSW	470	286	75	3.9	11.4	180	19
Curvado Glazed	Trans Roja		NSW	470	286	75	3.9	11.4	180	

This Data represents average results from commercial production lots.
 If specific test results are required, sample should be taken from current production lots.
 AUSTRALIAN STANDARD TEST METHODS AS/NSZ 4456 ARE USED AS APPLICABLE.
 Please note: FRL applies up to 3m high - restrained on top and bottom.

